



Siena Nylon Carpet Specifications: CLIFF

Style Name	CLIFF
Style Number	77
SPECIFICATIONS	
Construction	Textured Loop
Yarn Content	Zeftron® SD Nylon
Dye Method	Solution
Stitch Count	11 S.P.I.
Yarn Weight Tufted	23 oz./yd.2 (847 g./m.2)
Finished Pile Thickness	.128in (3.25 mm.)
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Polypropylene
Recycled Content	N/A
Width	12 Feet (3.66 m.)
Pattern Repeat	36" x 33"
Tile Size	N/A
PERFORMANCE	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# GLP2049
WARRANTIES	
Wear	10 Year Limited*
Stain, Static and Colorfastness	Lifetime Limited*
	*See website for full warranties
ADDITIONAL INFORMATION	
Backing Options	Contact Sales Representative
Custom Colors	Contact Sales Representative
Environmental	Proud member of the EPA's Green Power Partnership
RECOMMENDED INSTALLATION(S)	



Siena Nylon Carpet Specifications: CLIFF

Style Name	CLIFF TILE
Style Number	77T
SPECIFICATIONS	
Construction	Textured Loop
Yarn Content	Zeftron® SD Nylon
Dye Method	Solution
Stitch Count	11 S.P.I.
Yarn Weight Tufted	23 oz./yd.2
Primary Backing	Vinyl compound
Secondary Backing	Vinyl compound with recycled material
Width	N/A
Pattern Repeat	N/A
Tile Size	18" W x 36" L , 24" W x 24" L
PERFORMANCE	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# 2049
WARRANTIES	
Nexterra®	Lifetime Limited*
Wear	Lifetime Limited*
Stain, Static and Colorfastness	Lifetime Limited*
	*See website for full warranties
ADDITIONAL INFORMATION	
Backing Options	Contact Sales Representative
Custom Colors	Contact Sales Representative
Environmental	Proud member of the EPA's Green Power Partnership, UL Certified
Sustainability	Certification ANSI/NSF 140 Gold
RECOMMENDED INSTALLATION(S)	
	Herringbone, Monolithic, Ashlar