



## Siena Nylon Carpet Specifications: DUNE

Style Name	<b>DUNE</b>
Style Number	78
<b>SPECIFICATIONS</b>	
Construction	Textured Loop
Yarn Content	Zeftron® SD Nylon
Dye Method	Solution
Stitch Count	11 S.P.I.
Yarn Weight Tufted	23 oz./yd.2 (847 g./m.2)
Finished Pile Thickness	.128in (3.25 mm.)
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Polypropylene
Recycled Content	N/A
Width	12 Feet (3.66 m.)
Pattern Repeat	36" x 43.5"
Tile Size	N/A
<b>PERFORMANCE</b>	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# GLP2049
<b>WARRANTIES</b>	
Wear	10 Year Limited*
Stain, Static and Colorfastness	Lifetime Limited*
	*See website for full warranties
<b>ADDITIONAL INFORMATION</b>	
Backing Options	Contact Sales Representative
Custom Colors	Contact Sales Representative
Environmental	Proud member of the EPA's Green Power Partnership
<b>RECOMMENDED INSTALLATION(S)</b>	



## Siena Nylon Carpet Specifications: DUNE

Style Name	<b>DUNE TILE</b>
Style Number	78T
<b>SPECIFICATIONS</b>	
Construction	Textured Loop
Yarn Content	Zeftron® SD Nylon
Dye Method	Solution
Stitch Count	11 S.P.I.
Yarn Weight Tufted	23 oz./yd.2
Primary Backing	Vinyl compound
Secondary Backing	Vinyl compound with recycled material
Width	N/A
Pattern Repeat	N/A
Tile Size	18" W x 36" L , 24" W x 24" L
<b>PERFORMANCE</b>	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# 2049
<b>WARRANTIES</b>	
Nexterra®	Lifetime Limited*
Wear	Lifetime Limited*
Stain, Static and Colorfastness	Lifetime Limited*
	*See website for full warranties
<b>ADDITIONAL INFORMATION</b>	
Backing Options	Contact Sales Representative
Custom Colors	Contact Sales Representative
Environmental	Proud member of the EPA's Green Power Partnership, UL Certified
Sustainability	Certification ANSI/NSF 140 Gold
<b>RECOMMENDED INSTALLATION(S)</b>	
	Herringbone, Monolithic, Ashlar